B26 SERIES

NEW!

Waterworks™

The thirst quenchers!™

- ✓ Available as Cool & Cold or Hot & Cold
- ✓ Designed to fit the Waterworks™ Aquanet® Filter, Self Fill Bottle or standard water bottles
- ✓ Lead free Waterways
- ✓ Stainless steel Reservoir
- ✓ Vandal resistant Taps
- ✓ Available in White, Black & Off White
- ✓ 36 Month Comprehensive Warranty

3 YEAR WARRANTY

B26 SERIES

GENERAL FEATURES

The newest addition to our range of bottle top coolers, boasting the high level of quality Waterworks™ is renowned for. The B26 is sure to be a new favourite!

COLD TANK: 3.6 litre hygienic type 304 stainless steel for superior chilling. The highly polished surface is easy to clean and maintain.

HOT TANK: 1.8 litre type 304 stainless steel tank with 500 watt sheathed heater to ensure temperature control. The on/off switch is easily accessible at the back of the unit.

CABINET: Available in white, black & off white. The top and front panels are moulded UV treated ABS. The side panels are made from zinc coated steel sheets covered in polymer polyester resin.

TAPS: NSF Approved durable polypropylene self-closing design. Fully recessed, lever type for fast flow. Hot safety tap comes as standard on hot/cold model. Optional hygienic push taps also available.

OPTIONAL EXTRAS

SELF-FILL BOTTLE: A flexible filtration option for home, office or factory. Just fill with tap water for a continuous supply of fresh water. The SFB is the perfect partner for all bottled coolers and ceramic dispensers.

AQUANET®: Simply remove the no-spill spike and replace with a scuff ring (SR5) to provide a base for the Waterworks™ Aquanet® (AN2) and bottle. Ask us about the Non-splash Valve which is ideal for the set up.

NON SPLASH VALVE: Allows the bottle to be change without excess spillage. After putting the NSV on the bottle, simply place the bottle on the cooler and the valve opens to let water through. When removing the bottle, the valve closes automatically.

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled static type with no moving parts.

PERFORMANCE

Tap 1	Approx. 4-10°C
Tap 2	Room Temperature
Hot tap	Approx. 84-89°C

CAPACITY

ROOM TEMP °C	21	27	32
150ML CUPS/HR 10°C	44	32	18
LITRES/HR AT 10°C	4.2	3.1	1.8
HOT WATER DELIVERY: 45 x 170ml cups per hour			

*Intermittent use only, continuous use will result in reduced performance.

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
B26C	17kg	B26CH	18kg	33cm	33cm	100cm

WARRANTY

The Waterworks™ B26 Series water coolers are covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.

Damage to the stainless steel tank may occur if using reverse osmosis or incorrect filtration.

Warranty will be void in the event of this happening.

Please discuss filtration options with your local water filter specialist.

Distributed by PASLR

PASLR
Your Crucial Services. Sorted.

Waterworks™ Australia
ABN 91 902 793 936
48-50 Neumann Road Capalaba Queensland 4157
Bulk Warehouse: 53 Neumann Road Capalaba Queensland 4157

Phone (07) 3390 3777
Email sales@waterworksaustralia.com
www.waterworksaustralia.com

As part of Waterworks™ Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.